




PIONEERING INSULATED  
METAL PANEL TECHNOLOGY

# COLORS

## FOR THE COMMERCIAL & INDUSTRIAL MARKET


### STANDARD I EXTERIOR COLORS

Fluropon® Full-Strength 70% PVDF Fluoropolymer Coating




Polar White

R: .70 E: .86 SRI: 85




Sandstone

R: .60 E: .86 SRI: 71




Regal Gray

R: .55 E: .86 SRI: 64



Brownstone

R: .47 E: .88 SRI: 54



Almond

R: .63 E: .87 SRI: 75

Standard I & II Colors in 22 Ga. will incur an additional material charge. Please inquire.

### STANDARD II EXTERIOR COLORS

Fluropon® Full-Strength 70% PVDF Fluoropolymer Coating

### PREMIUM I EXTERIOR COLORS

Fluropon® Full-Strength 70% PVDF Fluoropolymer Coating




Harbor Blue

R: .28 E: .85 SRI: 27




Pacific Blue

R: .29 E: .87 SRI: 30



Colonial Red

R: .34 E: .87 SRI: 36



Brite Red

R: .49 E: .87 SRI: 56




Slate Gray

R: .37 E: .88 SRI: 41



Tundra

R: .46 E: .88 SRI: 52



Snow White

R: .65 E: .87 SRI: 78




Natural Patina

R: .41 E: .88 SRI: 46



Spruce

R: .36 E: .88 SRI: 39



Hunter Green

R: .35 E: .87 SRI: 37



Classic Green

R: .27 E: .87 SRI: 27



Medium Bronze

R: .33 E: .87 SRI: 35



Terra Cotta

R: .38 E: .87 SRI: 41



Smoke Gray

R: .50 E: .86 SRI: 57



Aegean Blue

R: .29 E: .86 SRI: 29



Gallery Blue

R: .28 E: .85 SRI: 27

### PREMIUM II METALLIC & PEARLESCENT EXTERIOR COLORS

Fluropon Classic® & Fluropon Classic® II: Full-Strength 70% PVDF Fluoropolymer Coatings



Weathered Zinc

R: .38 E: .87 SRI: 41



Copper Metallic

R: .46 E: .85 SRI: 51



Silver Metallic

R: .52 E: .80 SRI: 58



Champagne

R: .40 E: .85 SRI: 43



Dark Gray Metallic

R: .35 E: .84 SRI: 36

Metallic paint finishes will exhibit color shift, shade variances, striations and longitudinal patterning that are inherent characteristic and are not a product defect or cause for rejection.

## TUFF COTE® EXTERIOR COLORS


Tuff Cote® Fiber-Reinforced Polymer Coating – for Tuff Wall® or Tuff-Cast™ Panels only



Antique Bronze  
R: .26 E: .86 SRI: 25



Light Gray  
R: .35 E: .86 SRI: 37



Light Stone ■  
R: .51 E: .85 SRI: 58



Medium Beige  
R: .39 E: .86 SRI: 42



Surrey Beige  
R: .32 E: .87 SRI: 33



Textured White  
R: .64 E: .86 SRI: 77




Warm Limestone  
R: .45 E: .87 SRI: 51


■ Light Stone - Tuff Cote® does not match the Light Stone - Standard SP color offering.

## STANDARD SP EXTERIOR COLORS


Siliconized Polyester



Winter White  
R: .59 E: .85 SRI: 69



Light Stone ■  
R: .50 E: .88 SRI: 58



Ash Gray  
R: .47 E: .90 SRI: 55

## PREMIUM SP EXTERIOR COLORS


Siliconized Polyester




Hawaiian Blue  
R: .32 E: .87 SRI: 33




Crimson Red  
R: .33 E: .89 SRI: 36




Fern Green  
R: .27 E: .88 SRI: 27




Saddle Tan  
R: .48 E: .88 SRI: 55




Desert Sand  
R: .42 E: .89 SRI: 48



Burnished Slate  
R: .28 E: .88 SRI: 29




Koko Brown  
R: .28 E: .88 SRI: 29



Charcoal Gray  
R: .27 E: .88 SRI: 27




Rustic Red  
R: .36 E: .88 SRI: 39




Solar White  
R: .74 E: .87 SRI: 91

## POLYESTER EXTERIOR COLORS

Igloo White is standard interior color for all panels



Igloo White  
R: .64 E: .87 SRI: 77



Polyester Polar White  
R: .58 E: .89 SRI: 69

R = Initial Solar Reflectivity (ASTM E903, C1549)

E = Emissivity (ASTM C1371 or E408)

SRI = Solar Reflective Index (ASTM E1980, based on medium wind speed)

All Metl-Span colors are formulated to provide maximum energy-efficiency and solar reflectivity. All standard available Premium I and Premium II colors have been formulated for maximum solar reflectance.

Prices will vary by color, gauge and quantity of metal. Please contact your Metl-Span representative for complete information. All colors shown here approximate actual finish colors as accurately as possible.

Fluoropon® and Fluoropon Classic® are registered trademarks of Valspar.



PIONEERING INSULATED  
METAL PANEL TECHNOLOGY

1720 Lakepointe Drive  
Suite #101

Lewisville, Texas 75057

TOLL-FREE: 877.585.9969

TEL: 972.221.6656

FAX: 972.420.9382

EMAIL: panel@metlspan.com

WEB: metlspan.com

ENVIRONMENTALLY  
CONNECTED

